

I claim

1. Housing for hearing devices or hearing aids
5 respectively with sound amplifying components arranged at the inside of the housing, at least one opening (3) arranged at the outside of the housing and a removable cap (4) for covering said opening (3), whereby the cap (4) is a one-piece element with outwardly protruding pins (5) and
10 that grooves (6) are provided at the housing in the region of the opening (3) with outwardly acting dead stops such as said pins (5) are insertable into the grooves (6) from the inside of the housing but are jammed in direction of the outside by said dead stops.
- 15 2. Housing according claim 1 whereby the cap (4) in the area of the pins (5) consists of a rounded shape or of at least partially a cylindrical shape.
3. Housing according claim 1 whereby the pins (5) are arranged on the cap (4) lying in one axis and having
20 circular cross sections.
4. Housing according claim 1 whereby at least one clip (7) is resiliently arranged at the housing, the clip (7) being at least partially in resilient contact with the cap (4) in its inserted state and thereby forming a part of a
25 pivotable hinge of the housing.
5. Housing according claim 4 whereby the clip (7) is in contact with the cap (4) in the area of the pins (5).

6. Housing according claim 4 whereby the clip (7) is provided as part of the housing.

7. Housing according claim 1 whereby the housing consists of at least two detachable housing shells (1, 2).

5 8. Housing according claim 7 whereby the shells (1,2) consist of plastics.

9. Hearing device or hearing aid with a housing according to one of claims 1 to 8.